



13 Daniel street Kfar-Saba 44339 ISRAEL
Tel.: 972-9-7676678 Fax : 972-9-7656684 Direct phone No.: 972-522-335098
www.my-tech.co.il Info@my-tech.co.il

eMT3105P





13 Daniel street Kfar-Saba 44339 ISRAEL
Tel.: 972-9-7676678 Fax : 972-9-7656684 Direct phone No.: 972-522-335098

www.my-tech.co.il

Info@my-tech.co.il

Display	Display	10.4" TFT
	Brightness (cd/m2)	400
	Contrast Ratio	400:1
	Color	262K
	Resolution (W x H)	800x600
	Back Light	LED
	Back Light Life Time	>30,000 hrs
Processor	32Bit RISC CPU 800MHz	
Enclosure	Plastic	
Touch Panel	Touch Panel Type	4-wire Resistive Type
Memory	Storage	256 MB
	RAM (RAM)	256 MB
I/O ports	SD Card Slot	SD/SDHC
	USB Host	USB 2.0 x 1
	USB Client	USB 2.0 x 1
	Ethernet Port	10/100 Base-T
	COM Port	COM1(RS-232/RS-485 2W/4W), COM3(RS-232/RS-485 2W) Supports MPI 187.
	Audio	Audio Line Out - 3.5 mm jack x 1
Power	CAN bus	CANopen Protocol
	Input Power	24±20% VDC
RTC	Power Consumption	800m A@24V
	Built-in	
Specification	Panel Cutout (W x H)	259 x 201 mm
	Weight (kg)	Approx. 1.6 kg
Certification	CE	Compilies with EN 55022:2006+A1:2007 , EN 61000-3-2:2006+A2:2009 .EN 6155024:1998+A1:2001+A2:2003
	FCC	Comply with FCC class A
	UL	UL508 Type 4X
Operation	Voltage Resistance	500VAC (1 min)
	Isolation Resistance	Exceed 50MΩ at 500VDC
	Vibration Endurance	10 to 25 Hz(X,Y,Z direction 2G 30 minutes)
	Protection Structure	IP65 front panel (O ring seal)
	Storage Temperature	-20°~60°C (-4°~140°F)
	Operating Temperature	0°~50°C (32°~122°F)
	Operation Humidity	10~90% RH (non-condensing)