



13 Daniel street Kfar-Saba 44339 ISRAEL
Tel.: 972-9-7676678 Fax : 972-9-7656684 Direct phone No.: 972-522-335098
www.my-tech.co.il Info@my-tech.co.il

MT6070iE





13 Daniel street Kfar-Saba 44339 ISRAEL
 Tel.: 972-9-7676678 Fax : 972-9-7656684 Direct phone No.: 972-522-335098
www.my-tech.co.il Info@my-tech.co.il

Display

Display	7" TFT
Brightness (cd/m2)	350
Contrast Ratio	500:1
Color	16M
Resolution (W x H)	800 x 480
Back Light	LED
Back Light Life Time	>30,000 hr.
Processor	Cortex A8 32Bit RISC 600MHz
Enclosure	Touch Panel
Touch Panel Type	4-wire Resistive Type

Memory

Storage	128 MB
RAM (RAM)	128 MB

I/O ports

SD Card Slot	N/A
USB Host	USB 2.0 x 1
USB Client	USB 2.0 x 1
Ethernet Port	N/A
COM Port	Com1: RS-232/RS-485 2w/4w, Com3:RS-485 2w
Audio	N/A

Power

Input Power	24±20% VDC
Power Consumption	350mA@24VDC
RTC Built-in Specification	
Panel Cutout (W x H)	192 x 138
Weight (kg)	Approx.0.6 kg

Certification

CE	EN 55022:2010 Class B EN 55024:2010 EN 61000-3-2:2006+A2:2009 EN 61000-3-3: 2007 CISPR 22:2009+A1:2010
----	--

Operation

Voltage Resistance	500VAC (1 min)
Isolation Resistance	Exceed 50MΩ at 500VDC
Vibration Endurance	10 to 25Hz(X,Y,Z direction 2G 30 minutes)
Protection Structure	NEMA4 / IP65
Storage Temperature	-20°~60°C (-4° ~ 140°F)
Operating Temperature	0° ~ 50°C (32° ~ 122°F)
Operation Humidity	10% ~ 90% @ 40°C (non-condensing)